

















RECORD OF SURVEY 37-23 SEC. 28, T.4S., R.30E., M.D.B.&M. COUNTY OF MONO STATE OF CALIFORNIA

- (A) NW COR. SEC. 28: FOUND A 2 IN. DIA. I.P. PROJECTING 15 IN. WITH A G.L.O. CAP MARKED 
- (B) N 1/4 COR. SEC. 28: NOT FOUND. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 18 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. 
- (C) NE COR. SEC. 28: FOUND A 2 IN. DIA. I.P. NO TAG. REPLACED WITH A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 30 IN. DIA. PINE BEARS N 34° 05' E, 50.7 FT. SOME SCRIBING VISIBLE IN AN OPEN BLAZE. G.L.O. RECORD IS 21 IN. DIA. PINE N 34° E, 76 LINKS (52.2 FT.). A STUMP HOLE FROM A DOWN 30 IN. PINE BEARS S 13° 44' W, 29.8 FT. SOME SCRIBING VISIBLE IN AN OPEN BLAZE. G.L.O. RECORD IS 40 IN. DIA. PINE S 12° W, 44 LINKS (29.0 FT.). A 18 IN. DIA. PINE BEARS S 32° 03' E, 82.1 FT. MARKED T4S R30E S27 BT. A 26 IN. DIA. PINE BEARS S 27° 57' W, 91.8 FT. MARKED T4S R30E S28 BT. RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. 
- (D) E 1/4 COR. SEC. 28: NOT FOUND. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG IN SPACE BETWEEN ROCKS AT THE NORTH END OF A ROCKY RIDGE. A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP ON TOP OF PIPE MARKED FROM WHICH, A 18 IN. DIA. PINE BEARS N 36° 51' E, 69.8 FT. MARKED 1/4 S 27 BT. A 22 IN. DIA. PINE BEARS N 36° 47' W, 52.6 FT. MARKED 1/4 S 28 BT. 
- (E) S E COR. SEC. 28: FOUND A 2 IN. DIA. I.P. PROJECTING 12 IN. WITH A G.L.O. CAP MARKED 
- (F) S 1/4 COR. SEC. 28: NOT FOUND. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 26 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 10 IN. DIA. PINE BEARS N 35° 58' W, 9.0 FT. MARKED 1/4 S 28 BT. A 15 IN. DIA. PINE BEARS S 79° 57' W, 13.7 FT. MARKED 1/4 S 33 BT. RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. 
- (G) W 1/16 COR. BETWEEN SEC'S. 28 AND 33: SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG IN ROCK MOUND AT THE NORTH END OF ROCK OUTCROP. A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP ON TOP OF PIPE MARKED FROM WHICH, A 14 IN. DIA. PINE BEARS N 69° 07' E, 90.2 FT. MARKED W 1/16 S 28 BT. A 16 IN. DIA. PINE BEARS S 42° 20' E, 22.9 FT. MARKED W 1/16 S 33 BT. A 1 IN. DIA. I.P. BEARS N 89° 34' E, 7.81 FT. NO RECORD. 
- (H) SW COR. SEC. 28: FOUND A 2 IN. DIA. I.P. 4 IN. BELOW NORMAL GROUND SURFACE WITH A G.L.O. CAP MARKED 
- (I) S 1/16 COR. BETWEEN SEC'S. 29 AND 28: FOUND A 1 IN. DIA. I.P. FLUSH WITH GROUND SURFACE WITH R.C.E. TAG NO. 10121 ON TOP AS PER RECORD OF SURVEY MAP BOOK 2, PAGE 81. THE CALCULATED LOCATION FOR THE COR. BEARS S 86° 15' W, 0.13 FT. NO MONUMENT SET.
- (J) W 1/4 COR. SEC. 28: NOT FOUND. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 24 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 7 IN. DIA. PINE BEARS N 41° 57' W, 97.7 FT. MARKED 1/4 S 29 BT. A 30 IN. DIA. PINE BEARS N 47° 03' E, 44.4 FT. MARKED 1/4 S 28 BT. RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. 
- (K) SW 1/16 COR. SEC. 28: SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 14 IN. INTO GROUND TO BEDROCK. A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP ON TOP OF PIPE MARKED FROM WHICH, A 7 IN. DIA. PINE BEARS N 18° 23' E, 59.6 FT. MARKED SW 1/16 S 28 BT. A 8 IN. DIA. PINE BEARS S 3° 36' E, 49.7 FT. MARKED SW 1/16 S 28 BT. A 1 IN. DIA. I.P. BEARS S 39° 46' W, 17.10 FT. NO RECORD. RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. 
- (L) S 1/16 COR. SEC. 28: FOUND A 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED AS PER RECORD OF SURVEY MAP BOOK 3, PAGE 72. NOT ACCEPTED AS S 1/16 COR. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 25 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED BEARS S 84° 03' E, 2.85 FT. A 19 IN. DIA. PINE BEARS S 52° 28' E, 113.8 FT. MARKED CS 1/6 S 28 BT. A 30 IN. DIA. PINE BEARS S 69° 50' W, 121.5 FT. MARKED CS 1/16 S 28 BT. 
- (M) C 1/4 COR. SEC. 28: CEMENTED A 2 IN. DIA. BRASS CAP IN DRILL HOLE ON ROCK OUTCROP MARKED FROM WHICH, A 7 IN. DIA. PINE BEARS S 34° 56' W, 34.6 FT. MARKED C 1/4 S 28 BT. A 9 IN. DIA. PINE BEARS N 65° 50' W, 29.4 FT. MARKED C 1/4 S 28 BT. 
- (N) N 1/16 COR. SEC. 28: FOUND A 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED AS PER RECORD OF SURVEY MAP BOOK 3, PAGE 72. NOT ACCEPTED AS N 1/16 COR. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 30 IN. INTO GROUND WITH A 3 1/4 DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED BEARS S 13° 15' E, 0.61 FT. A 17 IN. DIA. PINE BEARS S 16° 30' W, 184.1 FT. MARKED CN 1/16 S 28 BT. A 14 IN. DIA. PINE BEARS N 55° 31' W, 91.2 FT. MARKED CN 1/16 S 28 BT. 
- (O) NE 1/16 COR. SEC. 28: FOUND 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED AS PER RECORD OF SURVEY MAP BOOK 3, PAGE 72. NOT ACCEPTED AS NE 1/16 COR. SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 25 IN. INTO GROUND WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED BEARS S 79° 36' E, 0.41 FT. A 8 IN. DIA. PINE BEARS N 26° 39' E, 9.5 FT. MARKED NE 1/16 S 28 BT. A 14 IN. DIA. PINE BEARS S 53° 04' E, 45.7 FT. MARKED NE 1/16 S 28 BT. RAISED A MOUND OF STONE 3 FT. DIA. AT BASE AROUND PIPE TO TOP. 
- (P) E 1/16 COR. SEC. 28: SET A 2 IN. DIA. ALUMINUM PIPE 30 IN. LONG 27 IN. INTO ROCK MOUND ON TOP OF SMALL ROCKY RIDGE WITH A 3 1/4 IN. DIA. U.S. DEPT. OF AGRI. FOREST SERVICE CAP MARKED FROM WHICH, A 13 IN. PINE BEARS N 52° 53' E, 35.0 FT. MARKED CE 1/16 S 28 BT. A 24 IN. PINE BEARS S 27° 05' E, 62.5 FT. MARKED CE 1/16 S 28 BT. 
- (Q) SE 1/16 COR. SEC. 28: FOUND 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED AS PER RECORD OF SURVEY MAP BOOK 3, PAGE 72. NOT ACCEPTED AS SE 1/16 COR. CEMENTED A 2 IN. DIA. BRASS CAP IN DRILL HOLE ON ROCK OUTCROP MARKED FROM WHICH, A 1 1/2 IN. DIA. I.P. WITH R.C.E. TAG NO. 10467 ATTACHED BEARS N 63° 24' 32" W, 52.52 FT. A 5/8 IN. DIA. STEEL REBAR SET IN DRILL HOLE BEARS N 77° 46' E, 2.55 FT. NO RECORD. A 17 IN. DIA. PINE BEARS N 21° 44' E, 42.4 FT. MARKED SE 1/16 S 28 BT. A 15 IN. DIA. PINE BEARS S 69° 16' W, 78.8 FT. MARKED SE 1/16 S 28 BT. 

Book 1 Page 2 of 2 R/S Maps